

COLORS		e LEED .
A (ALMOND)	B (BEIGE)	TO (DOVE GREY)
W (WHITE)	GB (GREIGE)	G (GREY)
DG (DARK GREY)		

DESCRIPTION

Re-Micron by *Imola* is a full body porcelain stoneware collection ideal for your architectural project. *Re-Micron* is a collection of tiles offered in subtle patterns, many hues and three finishes (polished, natural and bush-hammered). A collection of tiles to be craftily coordinated with one and other.

EXT

INT

FORMATS (Rectified monocaliber tiles)

NATURALE RT (NAT. RT): 30x30 cm | 30x60 cm | 60x60 cm LEVIGATO RT (LEV. RT): 30x60 cm | 60x60 cm BOCCIARDATO RT (BOC. RT): 30x60 cm | 60x60 cm

APPLICATIONS

Re-Micron is ideal for an interior and exterior application on floors and walls in your residential and commercial projects.

TECHNICAL INFORMATION

	444	<u>#</u>		<u>*</u>		ــــــــــــــــــــــــــــــــــــــ	<u></u>
	WATER ABSORPTION	FROST RESISTANCE	CHEMICAL RESISTANCE	RÉSISTANCE À L'ABRASION	STAIN RESISTANCE	SLIP RESISTANCE	RECYCLED CONTENT
NOKMES	ISO 10545/3	ISO 10545/12	ISO 10545/13	10545/6	ISO 10545/14	DIN51130- D.C.O.F. DIN51097 ANSI 137.1-2012	LEED CREDIT MR 4
VALEUKS	≤0,10%	RESISTANT	UA ULA	140 mm³	CLASS 5	NAT: R9 A NAT.: >0,42 LEV.: — LEV.: — BOC.: R11 B+C BOC.: >0,42	PRE-CONS.: G, DG, TO 32,3% ⁽¹⁾

INSTALLATION AND MAINTENANCE

To simplify laying operations and ensure the product looks its best, it is suggested to lay with joints of 2 mm for monoformats and of 3 mm to combine mixed formats. ■ Use high quality adhesive and grout from a manufacturer such as Mapei,following manufacturer's recommendations and depending on site conditions. ■ As soon as the joints have fully set, it is advisable to proceed to the initial post-construction cleaning as described by the manufacturer. ■ Daily maintenance can be performed with a neutral detergent.





<section-header>NOUDLE FIRED WALL THE COUDLE FIRED WALL THE COLORS CALORS AMOND RE-COLOUR CALORS AMOND CALORS CALORS

DESCRIPTION

Re-Colour by *Imola* is a collection of double fired wall tiles that marvellously completes the *Re-Micron* collection. Of the same caliber as *Re-Micron*, the *Re-Colour* collection is for spaces aspiring to present an actualized minimalistic design.

FORMATS (Rectified monocaliber tiles)

GLOSSY RT: 30x60 cm

APPLICATIONS

Re-Colour is suitable for interior walls, in your residential and commercial projects.

TECHNICAL INFORMATION

	444	<u>*</u>	<u>*</u>	<u> </u>		<u></u>
	WATER ABSORPTION	BENDING STRENGTH / MODULUS OF RUPTURE	CRAZING RESISTANCE	CHEMICAL RESISTANCE	STAIN RESISTANCE	RECYCLED CONTENU
NORMES	ISO 10545/3	ISO 10545/4	ISO 10545/11	ISO 10545/13	ISO 10545/14	LEED CREDIT MR 4
VALEURS	>10%	R > 17N/mm2 S ≥ 600 N	RESISTANT	GA GLA	CLASS 5	PRE-CONS.: 5,5%

INSTALLATION AND MAINTENANCE

It is suggested to lay tiles with a joint of 2-3 mm. Use high quality adhesive and grout from a manufacturer such as Mapei, following manufacturer's recommendations and depending on site conditions. As soon as the joints have fully set, it is advisable to proceed to the initial post-construction cleaning. Daily maintenance can be performed with a neutral detergent.



