

NEW PRODUCT



COLORED BODY PORCELAIN STONEWARE



BURLINGTON


COLORS



IVORY



SAND



GREY

DESCRIPTION

Burlington by 41zero42 is a colored body porcelain stoneware perfectly imitating the wide variation in color and veining specific to natural stone. *Burlington* is available in three colors with a unique format, allowing multiple installation patterns and color combinations. This ceramic rich in details will give a warm and harmonious look to your spaces.

FORMAT (Rectified tiles)

NATURAL RT: 15x90 cm

APPLICATIONS

Burlington is ideal for an interior application on floors and walls in your residential and commercial projects.

TECHNICAL INFORMATION

	WATER ABSORPTION	FROST RESISTANCE	PEI ABRASION RESISTANCE	CHEMICAL RESISTANCE	STAIN RESISTANCE	SLIP RESISTANCE
NORMS	ISO 10545/3	ISO 10545/12	ISO 10545/7	ISO 10545/13	ISO 10545/14	DIN51130- DIN51097
VALUES	0,3 %	RESISTANT	5	CONFORM	CLASS 5	D.C.O.F. ANSI 137.1-2012 (>0,42)
						CONFORM



INSTALLATION AND MAINTENANCE

It is suggested to lay tiles with a joint of 2-3 mm. Use high quality adhesive and grout from a manufacturer such as Mapei, following manufacturer's recommendations and depending on site conditions. It is recommended that you lay the rectangular formats side by side or offset by 2/3. Fixing in a 50% staggered configuration is not advised. As soon as the joints have fully set, it is advisable to proceed to the initial post-construction cleaning as described by the manufacturer. Daily maintenance can be performed with a neutral detergent. Daily maintenance can be performed with a neutral detergent, the use of abrasive cleaners is not recommended. During installation, it is essential to mix tiles from at least 3 different boxes to obtain a result of random patterns.

ciot

ciot.com



		
		MOSAICO*
METRIC	15 x 90 cm	3 x 15 cm
NOMINAL	6 x 36" NAT. RT	1 1/4 x 6" NAT.
GREY	●	●
IVORY	●	●
SAND	●	●

AVAILABILITY ¹

- stock
- special order
- N/A not available

¹ Subject to change

*1 ft²/sheet

Special pieces available, consult your sales representative.

THICKNESS: 10 mm

ICONS LEGEND

APPLICATION



Interior



Exterior



Wall



Floor

USE



Residential



Commercial



Industrial

FROST



Frost resistant

SLIP RESISTANCE RATE



Low



R10



R11



R12

High

SHADE VARIATION



Low



V2



V3



V4

High

ENVIRONMENT



LEED norm



Ecolabel norm

In the event of discrepancy with the official information of the manufacturer, the latter shall prevail.