

PROGETTO ITALIANO <b>+1 zero 42</b>	<b>PRODUCT DATASHEET</b>		Rev. n° 1 Data: 25/06/2013
	Intended use of the material: floor and wall tiles for interior and exterior		Date: 01/10/2012
<b>Type of material:</b> Unglazed porcelain stoneware tiles, dry pressed, format 15x90 cm (W= 147x895 x 10 mm) rectified		Group BIa UGL - Annex G EN 14411:2012	
Series Name: <b>BURLINGTON</b>			
Article: <b>GREY, IVORY; SAND</b>			
	Kind of test	Referring standard	Standard Value
Dimensions	Length and width tolerances	UNI EN ISO 10545-2	± 0,6%; ± 2,0 mm
	Thickness Tolerances		± 5%; ± 0,5 mm
	Tolerance straightness of the sides		± 0,5%; ± 1,5 mm
	Squareness and flatness tolerances		± 0,5%; ± 2,0 mm
Physical Properties	Water absorption E <sub>b</sub>	UNI EN ISO 10545-3	≤ 0,5 %
	Determination of breaking strength	UNI EN ISO 10545-4	≥ 1300 N
	Determination of modulus of rupture	UNI EN ISO 10545-4	≥ 45 N/mm <sup>2</sup>
	Determination of resistance of deep abrasion	UNI EN ISO 10545-6	145 mm <sup>3</sup>
	Determination of resistance to surface abrasion	UNI EN ISO 10545-7	PEI V
	Thermal Shock resistance	UNI EN ISO 10545-9	resistant
	Crazing Resistance	UNI EN ISO 10545-11	resistant
	Frost resistance	UNI EN ISO 10545-12	resistant
	Determination of slip resistance	DIN 51130	R10
		DCOF	0,69
Chemical Properties	Stain resistance - class	UNI EN ISO 10545-14	5
	Resistance to low concentrations of acids and alkalis	UNI EN ISO 10545-13	GLA
	Resistance to high concentrations of acids and alkalis		GHB
	Resistance to household chemicals and swimming pool salts		GA

Examiner  
  
Dr. Zucchi Massimo