NEW PRODUCT





DESCRIPTION

Marvel Edge by *Atlas Concorde* is a colored body porcelain stoneware collection available in eight colors. The look of natural stone such as travertine, agate and marble is recreated and allows for bold or more subtle décors. With a vast choice of mosaics and décors with golden detailing in the wall tiles, *Marvel Edge* gives an opportunity to create stunning interiors.

FORMATS (Rectified monocaliber tiles)

LAPPATO RT (LAP. RT): 120x278 cm | 120x240 cm | 120x120 cm | 75x150 cm | 75x75 cm | 45x90 cm | 60x60 cm | 30x60 cm NATURAL RT (NAT. RT): 60x60 cm | 30x60 cm

APPLICATIONS

Marvel Edge is ideal for an interior application on walls and floors, in residential and commercial projects (light traffic).

TECHNICAL INFORMATION

		WATER ABSORPTION	<u>業</u> FROST RESISTANCE	ABRASION RESISTANCE	BENDING STRENGTH	CHEMICAL RESISTANCE	STAIN RESISTANCE		SLIP STANCE
ſ	NORMS	ISO 10545/3 ≤ 0.5 %	ISO 10545/12	ISO 10545/6 175 mm³ max.	ISO 10545/4 35 N/mm² min.	ISO 10545/13	ISO 10545/14 min. CLASS 3	DIN51130- DIN51097	D.C.O.F. ANSI 137.1-2012 (>0,42)
	VALUES	< 0,1 %	RESISTANT	≤ 150 mm³	≥ 40 N/mm²	LAP. RT : UA ULA NAT. RT : UA ULA UHA	CLASS 5	LAP. RT : — NAT. RT : R9 A	LAP. RT : NOT CONFORM NAT. RT : CONFORM

INSTALLATION AND MAINTENANCE

It is suggested to lay tiles with a joint of 3-4 mm. Use high quality adhesive and grout from a manufacturer such as Mapei, following manufacturer's recommendations and depending on site conditions. As soon as the joints have fully set, it is recommended to proceed to initial cleaning with a neutral pH detergent. Daily maintenance can be performed with a neutral detergent. When installing, mix the content of several boxes to ensure even distribution of the tile shading.



DESCRIPTION

Marvel Edge Wall by *Atlas Concorde* is a white body wall tile collection available in five colors. When combined with the floor tiles, *Marvel Edge Wall* will bring elegance and a dreamlike quality to your décor.

IMPERIAL WHITE

ROYAL CALACATTA

FORMATS (Rectified monocaliber tiles) LUCIDO RT (LUC. RT) : 50x110 cm | 40x80 cm

APPLICATIONS

Marvel Edge Wall is ideal for an interior application on walls in residential and commercial projects.

TECHNICAL INFORMATION

	444 WATER ABSORPTION	<u>業</u> FROST RESISTANCE	BENDING STRENGTH	CHEMICAL RESISTANCE	STAIN RESISTANCE
NORMS	ISO 10545/3 ≤ 0.5 %	ISO 10545/12	ISO 10545/4 35 N/mm² min.	ISO 10545/13	ISO 10545/14 min. CLASS 3
VALUES	10% < E _v ≤ 20%	NOT RESISTANT	≥ 15 N/mm²	GA GLA GHA	CLASS 5

INSTALLATION AND MAINTENANCE

It is suggested to lay tiles with a joint of 3 mm. Use high quality adhesive and grout from a manufacturer such as Mapei, following manufacturer's recommendations and depending on site conditions. As soon as the joints have fully set, it is recommended to proceed to initial cleaning with a neutral pH detergent. Daily maintenance can be performed with a neutral detergent. When installing, mix the content of several boxes to ensure even distribution of the tile shading.





Rev.2018-12-12