




STONE FUSION

COLORS



MILK



COAL



CREAM



LEAD



GREY

DESCRIPTION

Stone Fusion by DOM is a colored-body porcelain stoneware with digital technology whose style suggests a fusion between wood and natural stone. The five neutral colors of *Stone Fusion* can easily blend with brightly colored furniture, like a red sofa, creating a classic look with a lively hint.

FORMATS (Rectified modular tiles and not rectified tiles)

NATURAL: 30x60 cm | 45,5x91 cm

NATURAL RT: 14,7x59,6 cm | 29,6x59,6 cm | 14,7x90 cm | 44,5x90 cm

LAPPATO RT: 14,7x59,6 cm | 29,6x59,6 cm | 14,7x90 cm | 44,5x90 cm

APPLICATIONS

Stone Fusion is ideal for an interior application on floors and walls in your residential and commercial (light traffic) projects. A great variation in color and patterns can be expected between the tiles, therefore it is very important to mix the contents of different boxes when installing.

TECHNICAL INFORMATION

	WATER ABSORPTION	FROST RESISTANCE	MOHS HARDNESS	PEI ABRASION RESISTANCE	CHEMICAL RESISTANCE	STAIN RESISTANCE	SLIP RESISTANCE	
NORMS	ISO 10545/3	ISO 10545/12	EN 101	ISO 10545/7	ISO 10545/13	ISO 10545/14	DIN51130- DIN51097	D.C.O.F. ANSI 137.1-2012 (>0,42)
VALUES	0,06 %	RESISTANT	NAT. : 8,5 LAP. : 5	4	GA GLA	CLASS 5	NAT.: R10 LAP.: -	CONFORM

INSTALLATION AND MAINTENANCE

It is suggested to lay tiles with a joint of 2 mm for the rectified formats and a joint of 3-4 mm for not rectified formats. ■ Use high quality adhesive and grout from a manufacturer such as Mapei, following manufacturer's recommendations and depending on site conditions. ■ For the 14,7x90 cm and 14,7x59,6 cm formats, it is recommended to lay the tiles in a soldier pattern or staggered by 10 to 20%. Fixing in a 50% staggered configuration is not advised. ■ As soon as the joints have fully set, it is advisable to proceed to the initial post-construction cleaning as described by the manufacturer. Daily maintenance can be performed with a neutral detergent.

STONE FUSION



COLORED BODY PORCELAIN STONEWARE / DIGITAL TECHNOLOGY

METRIC	14,7x59,6 cm		30x60 cm			14,7x90 cm		45,5x91 cm			5x5 cm
NOMINAL	6x24"		12x24"			5,9x35,5"		18x36"			2x2"
	NAT. RT	LAP. RT	NAT.	NAT. RT	LAP. RT	NAT. RT	LAP. RT	NAT.	NAT. RT	LAP. RT	NAT.
COAL	○	○	○	○	○	○	○	○	○	○	○
CREAM	○	○	●	○	○	●	○	○	○	○	○
GREY	○	○	●	○	○	●	○	○	○	○	○
LEAD	○	○	○	○	○	○	○	○	○	○	○
MILK	○	○	●	○	○	●	○	○	○	○	○

AVAILABILITY ¹

- in stock
- special order
- N/A not available

¹ Subject to change

Decors, listellos and special pieces available, consult your Ciot representative.
*1 ft²/sheet

THICKNESS: 10 mm

14,7x90 cm | 44,5x90 cm | 45,5x91 cm: **10,5 mm**

ICONS LEGEND

APPLICATION



Interior



Exterior



Wall



Floor

USE



Residential



Commercial



Industrial

FROST



Frost resistant

SLIP RESISTANCE



Low



R10



R11



R12

High

SHADE VARIATION



Low



V2



V3



V4

High

ENVIRONMENT



LEED™ norm



Ecolabel norm

In the event of discrepancy with the official information of the manufacturer, the latter shall prevail.

ciot

ciot.com